



Metriso® 3000 - test kit includes: digital high resistance tester, temperature and relative humidity sensor, USB port, PC software ETC for Windows®, 2 probes, a hand-held probe with connecting cable, user's instructions in German, English and French, calibration certificate, conductive carrying case fitted with dissipative pink foam.

- Suitable for resistance point-to-point and resistance to ground measurements
- Integrated data logger with USB communication port for data transmission (50.000 test values). The supplied Report Generating Software ETC allows to generate a complete test report
- Clip-on humidity and temperature sensor
- A barcode scanner can be used in order to record test points before testing

- Test voltage / Test current: $1 \text{ mA} \leq I \leq 1,3 \text{ mA}$
- Test range:

High ohmic range:	DC 10 volts, 100 volts and 500 volts
low ohmic range:	1 to 10 kOhm
High ohmic range:	1 kOhm to 1,2 TOhm
- Operation: Battery operated
- Probes:

2 x Model 850	(weight: 2,27 kg / Ø 63,5 mm)
with conductive rubber	
1 x hand-held probe Model 45	

complies with
 IEC 61340-4-1
 IEC 61340-2-3
 IEC 61340-4-5

Part Nr.

7100.3000.MK Metriso® 3000 Test Kit, menu language German/English/French/Spanish

7100.3000.G Metriso® 3000 Test Instrument only, menu language German/English/French/Spanish

Accessories

7100.2000.TR50 50 m extension cable for floor measurements

7100.2000.ML Replacement set of connecting cables (com/shield, +pole)

7100.3000.SC.2D Barcode-Scanner for 2D and 1D Codes