







WELLER IRON - PT SERIES TIPS

Suit WTCPS/T stations and TC series soldering pencils.

	600°F (315°C)	700°F (371°C)	800°F (427°C)	Description	Tip mm	Reach mm
	PTH6	PTH7	PTH8	Screwdriver	0.8	15.9
	PTA6	PTA7	PTA8	Screwdriver	1.6	15.9
	-	PTB7	PTB8	Screwdriver	2.4	15.9
	PTC6	PTC7	PTC8	Screwdriver	3.2	15.9
	PTD6	PTD7	PTD8	Screwdriver	4.7	15.9
	PTE6	-	PTE8	Screwdriver	6.0	15.9
	PTAA6	PTAA7	PTAA8	Single Flat	1.6	15.9
	PTBB6	PTBB7	PTBB8	Single Flat	2.4	15.9
	PTCC6	PTCC7	PTCC8	Single Flat	3.2	15.9
	-	PTDD7	PTDD8	Single Flat	4.7	15.9
	-	PTK7	PTK8	Long Screwdriver	1.2	25.4
	PTL6	PTL7	PTL8	Long Screwdriver	2.0	25.4
	-	PTM7	PTM8	Long Screwdriver	3.2	25.4
	PTR6	PTR7	PTR8	Narrow Screwdriver	1.6	15.9
	-	PTP7	PTP8	Conical	0.8	15.9
	PTT6	PTT7	PTT8	Conical	0.6	15.9
	-	PTF7	PTF8	Conical Flat	1.2	15.9
	PT06	PT07	PT08	Long Conical	0.8	25.4
	PTS6	PTS7	PTS8	Long Conical	0.4	25.4
	PTX6	PTX7	PTX8	Bent Slotted	0.8	
	PTZ6	PTZ7	-	Bent Slotted	0.5	